



GLOBAL
VACUUM PRESSES
shaping the world

GLOBAL **SUBLIMATION PRESS**

*Ideal solution for large format sublimation on hard substrates
Sublimation and thermoforming for different materials*



Nabuurs Developing S.L. | Pol. Industrial Moncada III
Avda. Paret del Patriarca, 4 | 46113 Moncada | Spain
Tel: +34 961 526 000 | Fax: +34 961 526 001
info@nabuurs.com | globalvacuumpresses.com

Global sublimation technology for the Sign-, Interior, Exterior and Engraving industry

Although people often think of fabrics or mugs when talking about sublimation, the Global sublimation press offers a much broader range of application. Global provides simple **3D and large format sublimation** for a variety of hard substrates, including **aluminium, acrylic stone, glass, metal sheeting, acrylic sheets (PMMA), textiles, wood (HPL, MDF, HDF).**

An absolute highlight of the machine is the 3D sublimation. Thanks to the unique vacuum heat technology

and elastic silicone membrane that precisely adapt to 3D shaped objects including the edges, it is now possible to sublimate in 3D up to a certain height. The sublimation press consists of contact heating platen combined with vacuum pressure technology and guarantees a gentle and homogeneous heat and pressure distribution throughout the entire surface of the material with **excellent sublimation print transfer results.**



Global Sublimation	G-SUB-1310	G-SUB-2510	G-SUB-3110	G-SUB-3710
Effective sublimation area	130 x 100 cm	250 x 100 cm	310 x 100 cm	370 x 100 cm
Total heating platen	145 x 115 cm	265 x 115 cm	325 x 115 cm	385 x 115 cm
Heating	Electrical heated platen	Electrical heated platen	Electrical heated platen	Electrical heated platen
Working temperature	0 - 200 °C			
Vacuum pump capacity	16 m³/h	25 m³/h	40 m³/h	40 m³/h
Vacuum pump mode	Continuous	Continuous	Continuous	Continuous
Max. vacuum pressure	8,5 t/m²	8,5 t/m²	8,5 t/m²	8,5 t/m²
Membrane	Silicone rubber	Silicone rubber	Silicone rubber	Silicone rubber
Air suction points	4	12	16	20
Electrical connection	380V / 3~ / 50 Hz			
Electrical consumption	5.75 kW	10.75 kW	13.75 kW	16.25 kW
Overall dimensions	161 x 137 x 126 cm	281 x 137 x 126 cm	341 x 137 x 126 cm	401 x 137 x 126 cm
Options				
Extra wide sublimation area with 130 cm	Yes	Yes	Yes	Yes
Vacuum tank with 400 litres	No	Yes	Yes	Yes
Two asymmetrical sublimation zones	No	Yes	Yes	Yes

Conditions

Delivery time: 8-10 Weeks
 Payment: 30 % in advance, 70% before dispatch
 Warranty: 2 Years under normal use, except silicone membrane

Prices and technical characteristics reserved to change without notice. Actual product may differ from image.