



Global Vacuum Press Professional

Professional vacuum membrane press

The Professional vacuum press model is especially designed for all trained woodworkers and craftsman who need a powerful vacuum press for woodworking and thermoforming during their day-to-day business and specific projects.

Equipped as standard with a 40 m³/h vacuum pump capacity, the membrane press offers ideal characteristics for professional woodworking and fulfils the minimum requirements for 3D thermoform applications. The rigid table frame construction and strong legs together with the 18 mm thick HPL compact press board ensure the highest stability, ensuring that even heavy moulds can be used.

The vacuum press further offers an efficient and convenient way to work thanks to the clearly arranged control panel, automatic vacuum pump mode and setting of the max. vacuum pressure. Typical press applications like profile wrapping, edge bending, wood panel veneering and laminating, as well as bending plywood in 2D and complicated 3D shapes, is not a problem for Global's Professional vacuum press.



Product information

- ▶ Vacuum pump with 40 m³/h
- ▶ Max. vacuum pressure up to 9 t/m²
- ▶ Setting of max. vacuum pressure, depending on the application
- ▶ Natural rubber and polyurethane membrane heat resistant up to 100 °C
- ▶ High volume membranes available (PU/SR)
- ▶ Vacuum ball valve for manual control of air evacuation
- ▶ Equipping with industrial caster wheels optional available
- ▶ Space saving folding model available
- ▶ Reliable rotary vane vacuum pump, maintenance-free
- ▶ Automatic or Continuous operating mode of the vacuum pump
- ▶ Available with natural rubber, polyurethane or silicone membrane
- ▶ Silicone membrane heat resistant up to 230 °C
- ▶ 18 mm HPL compact press board with up to 32 suction points
- ▶ Vacuum pressure display via analogue pressure gauge
- ▶ Vacuum tank with 500 l optional available
- ▶ Electrical connection 380 V / 50 Hz / 3~

Code	Total press area ¹	Membrane ²	Vacuum pump	Operating mode	Power consumption
GMP-P- / GTP-P-2513	2540 x 1290 mm	NR, PU, SR	40 m ³ /h	Automatic or Continuous	1.25 kW
GMP-P- / GTP-P-3113	3140 x 1290 mm	NR, PU, SR	40 m ³ /h	Automatic or Continuous	1.25 kW
GMP-P- / GTP-P-3713	3740 x 1290 mm	NR, PU, SR	40 m ³ /h	Automatic or Continuous	1.25 kW

¹ Inside dimensions of the membran frame

² NR = Natural rubber; PU = Polyurethane; SR = Silicone rubber

Conditions

Delivery time: 4 Weeks
 Shipping: Ex Works 46113 Moncada, Spain
 Warranty: 2 Years under normal use, except on membranes, vacuum bags and HPL pressboards
 Price and technical characteristics reserved to change without notice.

Nabuurs Developing S.L.

Pol. Industrial Moncada III | Avda. Pared del Patriarca 4 | 46113 Moncada | Spain
 Tel: +34 96 152 6000 | global@nabuurs.com | www.globalvacuumpresses.com
 VAT: ES-B96939095