



Global Vacuum Press Standard

Standard vacuum membrane press

The Standard press model is a cost-efficient vacuum frame press that provides ideal solutions for woodworking, such as wrapping, veneering, laminating and bending different kinds of wood without compromising quality. The press has been designed for individual and small to medium production capacities and is equipped with a continuously run vacuum pump as standard.

Typical press applications are profile wrapping, edge bending, wood panel veneering and laminating as well as bending plywood into 2D and 3D shapes. Equipped with a silicone membrane the press is also suitable for 2D thermoforming of acrylic solid surface material and similar composite materials.



Product information

- ▶ Vacuum pumps from 10 to 25 m³/h, optional 40 m³/h
- ▶ Max. vacuum pressure up to 9 t/m²
- ▶ Available with natural rubber, polyurethane or silicone membrane
- ▶ Silicone membrane heat resistant up to 230 °C
- ▶ 10 mm HPL compact press board with up to 10 suction points
- ▶ Vacuum pressure display via analogue pressure gauge
- ▶ Equipping with industrial caster wheels optional available
- ▶ Reliable rotary vane vacuum pump, maintenance-free
- ▶ Continuous operating mode of the vacuum pump, optional Automatic mode incl. vacuum pressure adjustment
- ▶ Natural rubber and polyurethane membrane heat resistant up to 100 °C
- ▶ High volume membranes available (PU/SR)
- ▶ Vacuum ball valve for manual control of air evacuation
- ▶ Vacuum tank with 100 l optional available
- ▶ European standard plug 220 V/50 Hz/1~

| Code | Total press area ¹ | Membrane ² | Vacuum pump | Power consumption |
|---------------------|-------------------------------|-----------------------|----------------------|-------------------|
| GMP-S- / GTP-S-1313 | 1310 x 1310 mm | NR, PU, SR | 10 m ³ /h | 0.40 kW |
| GMP-S- / GTP-S-2513 | 2560 x 1310 mm | NR, PU, SR | 16 m ³ /h | 0.55 kW |
| GMP-S- / GTP-S-3113 | 3160 x 1310 mm | NR, PU, SR | 25 m ³ /h | 0.80 kW |
| GMP-S- / GTP-S-3713 | 3760 x 1310 mm | NR, PU, SR | 25 m ³ /h | 0.80 kW |

¹ Inside dimensions of the membran frame

² NR = Natural rubber; PU = Polyurethane; SR = Silicone rubber

Conditions

Delivery time: 4 Weeks
 Shipping: Ex Works 46113 Moncada, Spain
 Warranty: 2 Years under normal use, except on membranes, vacuum bags and HPL pressboards
 Technical characteristics reserved to change without notice.

Nabuurs Developing S.L.

Pol. Industrial Moncada III | Avda. Pared del Patriarca 4 | 46113 Moncada | Spain
 Tel: +34 96 152 6000 | global@nabuurs.com | www.globalvacuumpresses.com
 VAT: ES-B96939095